

MTP-25 & MTP-85



Bluetooth Printer



2" Bluetooth Thermal Printer



3" Bluetooth Thermal Printer



3" Bluetooth Thermal Printer



USB



Bluetooth



Android



- 1 Small & comfortable to carry
- 2 Easy paper loading & User friendly with classic three-button
- 3 USB + Bluetooth interface (standard) + Android
- 4 LED indication facility available during abnormal condition of printer

SPECIFICATIONS OF WePMTP-25 & MTP-85



Features of MTP-25

- Drop in paper loading, easy operation.
- Support to print receipt during charging the battery.
- **Bluetooth** : BT3.0 and BLE4.0
- Support 1D barcode, QR barcode
- Support for printing different density bitmap and download graphics
- **Print Method** : Direct thermal line
- **Dot Density**: 384dot/line
- **Print Speed** : 60mm/s (Max)
- **Interface** : USB+Bluetooth(Standard)+Android
- **Paper Width** : 58mm
- **Paper Diameter** : 50mm
- **Print Commands** : Compatible with ESC/POS
- **Barcode Type** : UPC-A, UPC-E, EAN(JAN)13, EAN(JAN)8, CODE39, CODABAR, ITF, CODE93, CODE128, QR Code
- **Buffer** : Input buffer 4K bytes NV Flash 60K bytes
- **Dimension** : 148.5(L) X 86(W) X 58.5(H)mm
- **Weight (including battery)** : 288g
- **Power Adaptor** : Input - AC100-220V; Output - DC9V/1A
- **Battery** : 1800mA-A900mA, 7.4V rechargeable Li-ion Battery
- **Charging Time** : 2.5~3.5hours
- **Work Environment** : Temperature: 0 ~ 45°C; Humidity- 10 ~ 80%
- **Storage Environment** : Temperature: -10 ~ 60°C, Humidity- 10 ~ 90%
- **Printing Length** : 50KM

Features of MTP-85

- Drop in paper loading, easy operation.
- Support to print receipt during charging the battery.
- **Bluetooth** : BT3.0 and BLE4.0
- Support 1D barcode, QR barcode
- Support for printing different density bitmap and download graphics
- **Print Method** : Direct thermal line
- **Dot Density**: 576dot/line
- **Print Speed** : 60mm/s (Max)
- **Interface** : USB+Bluetooth (Standard) +Android
- **Paper Width** : 80mm
- **Paper Diameter** : 50mm
- **Print Commands** : Compatible with ESC/POS
- **Barcode Type** : UPC-A, UPC-E, EAN(JAN)13, EAN(JAN)8, CODE39, CODABAR, ITF, CODE93, CODE128, QR Code
- **Buffer** : Input buffer 4K bytes NV Flash 60K bytes
- **Dimension** : 131(L) X 107(W) X 58(H)mm
- **Weight (including battery)** : 350g
- **Power Adaptor** : Input - AC100-220V; Output - DC9V/1A
- **Battery** : 2200mA-A900mA, 7.4V rechargeable Li-ion Battery
- **Charging Time** : 3.0~5.0hours
- **Work Environment** : Temperature: 0 ~ 45; Humidity- 10 ~ 90%
- **Storage Environment** : Temperature: -10 ~ 50°C, Humidity- 10 ~ 90%
- **Printing Length** : 50KM



Dealer Name and Address



Version-1.0/Oct/2016