

# XP-3300E Series

www.posiflex.com

**POSIFLEX**  
Your Success is Our Vision



| Specification               | XP-3312H-E   | XP-3315H-E                         |
|-----------------------------|--|------------------------------------|
| Processor                   | Intel Pine View D425 1.8 G / 512 K Cache CPU or<br>Intel Pine View D525 1.8 G / 1 M Cache CPU (Dual Core) (Optional) |                                    |
| System Memory               | DDR3 800 MHz, SO-DIMM socket x 1, max 4 GB, default 1 GB   |                                    |
| Storage Device              | 2.5" SATA HDD or SSD (Optional)  |                                    |
| Power Supply                | 12V DC power, 120W   |                                    |
| Audio                       | Buzzer only  |                                    |
| OS support                  | Windows XP Pro / WEPOS / POSReady / Win 7 / Linux  |                                    |
| <b>Display</b>              |  |                                    |
| LCD                         | 12" TFT LCD, 1024 x 768 resolution   | 15" TFT LCD, 1024 x 768 resolution |
| Touch Function              | Resistive, 5-Wire, USB Interface   |                                    |
| Brightness Control          | By digital push button   |                                    |
| Tilt Adjustment             | From 14° to 55°  |                                    |
| <b>Connectivity</b>         |  |                                    |
| LAN Port                    | 10 / 100 / 1000 Mb   |                                    |
| Serial Port                 | DB9 x2, RJ-45x1 (Optional RJ-45 to DB9 cable), with 5V support on COM2/COM3,<br>12V support on COM2/COM3             |                                    |
| PS/2 Keyboard               | By internal cable (Optional)   |                                    |
| UPS Port                    | Yes, battery (Optional)  |                                    |
| Standard USB Port           | 4  |                                    |
| VGA Port                    | D-SUB, 15 pins, with 12V power for Posiflex LCD monitor  |                                    |
| CR Port                     | 1, control 2 CR  |                                    |
| <b>Printer</b>              |  |                                    |
| 3" Thermal Printer          | 150 mm/sec,<br>80 mm paper width   |                                    |
| Cutter                      | Auto cutter  |                                    |
| <b>Physical Dimension</b>   |  |                                    |
| Dimension (W x D x H in mm) | 325 X 386.2 X 298.1  | 375 X 386.2 X 395                  |
| Weight (N. W. in kg)        | 6.24   | 6.83                               |
| <b>Environment</b>          |  |                                    |
| Operation Condition         | 0°C - 40°C, 20%RH - 90%RH  |                                    |
| Storage Condition           | (-20°C) - 70°C, 10%RH - 90%RH  |                                    |
| <b>Options</b>              |  |                                    |
| MSR                         | Integrated, 2 or 3 tracks or JIS-II  |                                    |
| PD-2606U                    | VFD, 2 x 20, rear mount  |                                    |
| PD-330U                     | LCD, 2 x 20, rear mount  |                                    |
| PD-76X4                     | 240 x 64 dot graphics LCD, default 200 mm pole   |                                    |
| PD-2605 / PD-2605U          | VFD, 2 x 20, default 200 mm pole   |                                    |
| PD-309 / PD-309U            | LCD, 2 x 20, default 200 mm pole   |                                    |
| SSD                         | 8 G minimum  |                                    |
| LM/TM-2212                  | 12" 2nd LCD display or touch LCD display with attachment SD-300  |                                    |
| UPS Battery                 | 2300 mAh / 12V   |                                    |
| Certifications              |  |                                    |

# XP-3300E Series

## Advanced All-in-One Fan-Free POS Terminal



Design and Manufacturing In Taiwan by Posiflex Technology Inc.  
\*\* The product information and specifications are subject to change without prior notice.

2011 XP33Q2C1

**POSIFLEX** Posiflex Technology, Inc.  
Headquarters  
No.6, Wuquan Rd., Wugu Dist., New Taipei City  
248, Taiwan (R.O.C.)  
Tel: +886 2 2299-1599 Fax: +886 2 2299-1819  
sales@posiflex.com.tw www.posiflex.com

Authorized Distributor / Reseller

www.posiflex.com

## XP-3300E Series

Posiflex presents the fan-free XP-3300E series as an advanced all-in-one POS terminal. The XP-3300E series offers touch screen, printer and MSR in a tightly integrated package to bring retailers space-and-cost saving benefits. Adding Intel Pine View Dual Core 1.8GHz CPU and 1000Mb Ethernet that bring efficiency into daily operation, as well as plenty of ports such as USB, Serial, VGA and CR for a wide range of applications. With the well-executed design, the XP-3300E series showcases unmatched value.

XP-3300E series is all-in-one type with high performance for retailers to run mass transaction data.




### Key Features

- ▶ Resistive touch screen : 15" LCD 1280 x 1027 or 12" LCD 1024 x 768 resolution
- ▶ Equipped with Intel Pine View D525 Dual Core 1.8 GHz (Optional) and DDR3 memory
- ▶ All-in-one integrated system with touch screen, thermal printer and MSR (Optional) for space saving
- ▶ 3" thermal printer with auto cutter
- ▶ Fan-free design boasting quiet and anti-dust features
- ▶ Aluminum die casting design for efficient cooling
- ▶ Thermal printer with "one-button cutter blade retract" design to clear paper jam easily
- ▶ Special "drop-load" design for easy printer paper roll loading
- ▶ UPS (Embedded on main board developed by Posiflex) support to avoid sudden power loss (Optional)
- ▶ User-friendly mechanism for system upgrade and easy maintenance
- ▶ High quality, rock solid design with easy maintenance in mind



Adjustable LCD



With customer pole display



With rear mounted customer display



With MSR and finger print sensor



With 2nd display LCD

Resistive touch screen :  
15" or 12" LCD

Fan-free design boasting  
quiet and anti-dust features



3" thermal printer with  
auto cutter



System and printer status LEDs,  
power switch, brightness control  
buttons



Built-in magnetic stripe  
reader (MSR)